

D16 VICI ValcoPLOT® Capillary Columns

HayeSep® C

Divinylbenzene/Acrylonitrile

This phase is available exclusively from VICI.

Applications

C1-C3 hydrocarbons, C1-C5 hydrocarbons, Solvents

I.D. (mm)	Length (meter)	Film Thickness (µm)	Temperature Limits (°C)	Part Number	Price
Fused silica					
0.32	15	10	-60° to 250°C	CFS-PC1532-100	
	30	10	-60° to 250°C	CFS-PC3032-100	
0.53	15	20	-60° to 250°C	CFS-PC1553-200	
	30	20	-60° to 250°C	CFS-PC3053-200	
Stainless Steel					
0.53	30	20	-60° to 250°C	CSS-PC3053-200	

HayeSep® D

High Purity Divinylbenzene

This phase is available exclusively from VICI.

Applications

MAPP gas, C1-C5 hydrocarbons, Solvents

I.D. (mm)	Length (meter)	Film Thickness (µm)	Temperature Limits (°C)	Part Number	Price
Fused silica					
0.32	15	10	-60° to 270°C/290°C	CFS-PD1532-100	
	30	10	-60° to 270°C/290°C	CFS-PD3032-100	
0.53	15	20	-60° to 270°C/290°C	CFS-PD1553-200	
	30	20	-60° to 270°C/290°C	CFS-PD3053-200	
Stainless Steel					
0.53	30	20	-60° to 270°C/290°C	CSS-PD3053-200	

HayeSep® N

Divinylbenzene/Ethyleneglycoldimethacrylate

We highly recommend HayeSep A, which has similar retention characteristics but is made from higher purity raw materials.

I.D. (mm)	Length (meter)	Film Thickness (µm)	Temperature Limits (°C)	Part Number	Price
Fused silica					
0.32	15	10	-60° to 165°C	CFS-PN1532-100	
	30	10	-60° to 165°C	CFS-PN3032-100	
0.53	15	20	-60° to 165°C	CFS-PN1553-200	
	30	20	-60° to 165°C	CFS-PN3053-200	
Stainless Steel					
0.53	30	20	-60° to 165°C	CSS-PN3053-200	

HayeSep® P

Divinylbenzene/Styrene

This phase is available exclusively from VICI.

Applications

C1-C3 hydrocarbons, C1-C5 hydrocarbons, Solvents

I.D. (mm)	Length (meter)	Film Thickness (µm)	Temperature Limits (°C)	Part Number	Price
Fused silica					
0.32	15	10	-60° to 250°C	CFS-PP1532-100	
	30	10	-60° to 250°C	CFS-PP3032-100	
0.53	15	20	-60° to 250°C	CFS-PP1553-200	
	30	20	-60° to 250°C	CFS-PP3053-200	
Stainless Steel					
0.53	30	20	-60° to 250°C	CSS-PP3053-200	

HayeSep® Q

Divinylbenzene

We highly recommend HayeSep D, which has similar retention characteristics but is made from higher purity raw materials.

I.D. (mm)	Length (meter)	Film Thickness (µm)	Temperature Limits (°C)	Part Number	Price
Fused silica					
0.32	15	10	-60° to 250°C	CFS-PQ1532-100	
	30	10	-60° to 250°C	CFS-PQ3032-100	
0.53	15	20	-60° to 250°C	CFS-PQ1553-200	
	30	20	-60° to 250°C	CFS-PQ3053-200	
Stainless Steel					
0.53	30	20	-60° to 250°C	CSS-PQ3053-200	