

D68 Protocol Station Regulator

Protocol Station Regulator

Features

- Wall Mounted Regulator
- Convenient Safe Charging Gas Tanks
- 3' Stainless Steel Pigtail with Gas Cylinder Fittings
- Choice of Brass or Stainless Steel Construction
- Available with Single and Dual Stage Regulators

The Protocol Station is a regulator option designed for the convenient wall mounting of a Concoa High Purity regulator. Wall mounting of a regulator provides ease of use, prevents regulator damage and improves safety. The Protocol Station is available in brass or 316 Stainless Steel construction as specified by the regulator series. This option comes complete with a 3 foot long flexible all stainless steel pigtail with armor casing. The CGA connection on the pigtail has an integral check valve in the gland to prevent internal contamination during cylinder change out. Should purging be desired the gas block comes with a plugged port which can be removed for the assembly of a diaphragm valve. The bracket mounts conveniently to any surface.



Protocol Station Regulator

Materials of Construction

Gas Block:	316 Stainless Steel or Brass Barstock
Pigtail:	316 Stainless Steel inner- core 316 Stainless Steel Braid (2 layers) 304 Stainless Steel armor casing
CGA Connections:	316 Stainless Steel or Brass Barstock
Check Valve O'Ring	Viton (other materials available on request)

Specifications

Maximum Inlet Pressure:	3000 psi
Operating Temp. Range:	0° F to 120° F
Outlet Pressure Range:	0-100 psi
Inlet gauge:	0-4000 psi

Description	Part No.*	Price
Single stage Brass Barstock regulator with wall mount protocol station, 0-100 psi outlet, 3' stainless steel pigtails with CGA outlet to tank	4023321CGA580	
	4023321CGA350	
	4023321CGA590	
Dual stage Brass Barstock regulator with wall mount protocol station, 0-100 psi outlet, 3' stainless steel pigtails with CGA outlet to tank	4123321CGA580	
	4123321CGA350	
	4123321CGA590	
Single stage 316 Stainless Steel, regulator with wall mount protocol station, 0-100 psi outlet, 3' stainless steel pigtails with CGA outlet to tank	4223321CGA580	
	4223321CGA350	
	4223321CGA590	
Dual stage 316 Stainless Steel, regulator with wall mount protocol station, 0-100 psi outlet, 3' stainless steel pigtails with CGA outlet to tank	4323321CGA580	
	4323321CGA350	
	4323321CGA590	

*CGA Fitting

580
350
590

For Gases

Helium
Hydrogen
Air

Other fittings available on special request.